



**JD6-99.0 KW**  
**KEEL COOLED / WET MANIFOLD**  
USA 2009 COMPLIANT MODELS

MODEL		JD6-99.0 KW
ENGINE	<b>TIER 2</b>	JOHN DEERE 6068TFM76
CYLINDERS		SIX
CUBIC DISPLACEMENT		415 CID
BORE X STROKE		4.17 X 5.00
ASPIRATION		TURBO
FUEL CONSUMPTION @ 50 % LOAD		est. 4.1 GPH
FUEL CONSUMOTION @ 100 % LOAD		est. 7.2 GPH
NEWAGE		UCI 274 E
OUTPUT VOLTS		208, <b>Three Phase</b>
OUTPUT AMPS		274
FREQUENCY		60 HERTZ
DIMENSIONS		L 87.5 X W 34.0 X H 39.0"
WEIGHT		2903 LBS.

**STANDARD FEATURES**

- 12 Volt Electric Starter
- 12 Volt Battery Charging Alternator
- Automatic Engine Shutdown for Low Oil Pressure and High Coolant Temperature
- Fuel Filter
- Fuel Transfer Pump
- Air Silencer Intake-Cleaner
- Heavy Duty Steel Frame
- Single Bearing Generator
- Brushless Exciter
- Electronic Control Panel w / Display for all Engines and Generators Functions
- \$450.00 ( not included )

*Florida*  
2880 Hammondville Road  
Pompano Beach, Florida 33069  
Phone: (954) 979-5899  
Fax: (954) 979-4349

*Connecticut*  
900 Industrial Park Road. Suite #10  
Deep River, Connecticut 06417  
Phone: (860) 526-9773  
Fax: (860) 526-2090