

KK4-25.0 KW
KEEL COOLED / DRY EXHAUST

MODEL		KK4-25.0 KW
ENGINE	TURBO	KUBOTA V2003-T-BG
CYLINDERS		FOUR
CUBIC INCH DISPLACEMENT		121.99
BORE & STROKE		3.27 x 3.64
RPM		1800
DIMENSIONS		L 46" x W 23" x H 36"
WEIGHT	DRY	775 Lbs Shipping 957 Lbs
NEWAGE / STANFORD		BCI 184 F 60 HERTZ
OUTPUT VOLTS		120 / 240, Single Phase
OUTPUT AMPS		208.3 / 104.1
OUTPUT WATTS		25,000
EXHAUST DIA.		2.0" FLANGE
FUEL INLET		5/16
FUEL RETURN LINE		3/16

STANDARD FEATURES

- 12 Volt Electric Starter
- 12 Volt Battery Charging Alternator
- Automatic Engine Shutdown for Low Oil & High Coolant Temperature
- Fuel Filter
- Fuel Transfer Pump
- Air Intake-cleaner
- Heavy Duty Steel Frame
- Single Bearing Generator
- Brushless Exciter
- Start / Stop / Preheat
- Hourmeter

Florida
2880 Hammondville Road
Pompano Beach, Florida 33069
Phone: (954) 979-5899
Fax: (954) 979-4349

Connecticut
900 Industrial Park Road. Suite #10
Deep River, Connecticut 06417
Phone: (860) 526-9773
Fax: (860) 526-2090