

KK4-15.0 KW
KEEL COOLED / DRY EXHAUST

MODEL		KK4-15.0KW
ENGINE		KUBOTA V2003BG
CYLINDERS		Four (4)
CUBIC INCH DISPLACEMENT		122
BORE X STROKE		3.27" x 3.64"
RPM		1,800
DIMENSIONS		L 38" x W 21" x H 26"
WEIGHT	DRY	680 lbs Shipping 724 Lbs
NEWAGE BCI 184D		Single Phase / 60 Hertz
OUTPUT VOLTS		120 / 240
OUTPUT AMPS		117 / 58.5
OUTPUT WATTS		15,000
EXHAUST DIA.		2.0" Flange Female NPT
FUEL INLET		5/16
FUEL RETURN		.3/16

STANDARD FEATURES

- 12 Volt Electric Starter
- 12 Volt Battery Charging Alternator
- Automatic Engine Shutdown for Low Oil Pressure & High Coolant Temp
- Fuel Filter
- Fuel Transfer Pump
- Air Silencer Intake-Cleaner
- Heavy Duty Steel Frame
- Single Bearing Generator
- Brushless Excitor
- Start / Stop / Preheat
- Hourmeter

Florida
2880 Hammondville Road
Pompano Beach, Florida 33069
Phone: (954) 979-5899
Fax: (954) 979-4349

Connecticut
900 Industrial Park Road, Suite #10
Deep River, Connecticut 06417
Phone: (860) 526-9773
Fax: (860) 526-2090