

KK3-6.0 KW
KEEL COOLED / DRY EXHAUST

MODEL	KK3-6.0 KW
ENGINE	KUBOTA D1005
CYLINDERS	Three (3)
CUBIC INCH DISPLACEMENT	61
BORE / STROKE	2.99 x 2.90
RPM	1,800
DIMENSIONS	L 34." x W 22 1/2 x H 29"
WEIGHT	460 Lbs
NEWAGE	PIO4461J Single Phase / 60 Hertz
OUTPUT VOLTS	120 / 240
OUTPUT AMPS	70 / 35
OUTPUT WATTS	6,000
EXHAUST DIA.	1.5" inch Flange Female NPT
FUEL LINE DIA.	5/16"
RETURN DIA.	3/16"

Standard Features

- 12 Volt Electric Starter
- 12 Volt Battery Charging Alternator
- Automatic Engine Shutdown for Low Oil Pressure & High Cooland Temp
- Fuel Filter
- Fuel Transfer Pump
- Air Intake Cleaner / Silencer
- Heavy Duty Steel Frame
- Single Bearing Generator
- Brushless Excitor
- Start / Stop / Preheat
- Hourmeter

Florida
2880 Hammondville Road
Pompano Beach, Florida 33069
Phone: (954) 979-5899
Fax: (954) 979-4349

Connecticut
900 Industrial Park Road. Suite #10
Deep River, Connecticut 06417
Phone: (860) 526-9773
Fax: (860) 526-2090