

KK4-21.0 KW

KEEL COOLED / DRY EXHAUST

MODEL	KK4-21.0 KW
ENGINE	KUBOTA V2403
CYLINDERS	Four (4)
CUBIC INCH DISPLACEMENT	148.5
BORE X STROKE	3.43" X 4.03"
RPM	1,800
DIMENSIONS	L 43.25" x W 21" x H 26"
WEIGHT	775 lbs Shipping Wt. 957 Lbs
NEWAGE / STANFORD	PI144D1J 60 Hertz
OUTPUT VOLTS	120 / 240, Single Phase
OUTPUT AMPS	175 / 87.5
OUTPUT WATTS	21,000
EXHAUST DIAM.	2.0" Flange Female NPT
FUEL LINE	5/16
FUEL RETURN	3/16

STANDARD FEATURES

- **12 Volt Electric Starter**
- **12 Volt Battery Charging Alternator**
- **Automatic Engine Shutdown for Low Oil Pressure & High Coolant Temp**
- **Fuel Filter**
- **Fuel Transfer Pump**
- **Air Silencer Intake-Cleaner**
- **Heavy Duty Steel Frame**
- **Single Bearing Generator**
- **Brushless Excitor**
- **Start / Stop / Preheat**
- **Hourmeter**

Florida
2880 Hammondville Road
Pompano Beach, Florida 33069
Phone: (954) 979-5899
Fax: (954) 979-4349

Connecticut
900 Industrial Park Road. Suite #10
Deep River, Connecticut 06417
Phone: (860) 526-9773
Fax: (860) 526-2090