

KK4-21.0 KW
KEEL COOLED / DRY EXHAUST

MODEL	KK4-21.0 KW
ENGINE	Kubota V 2203
CYLINDERS	Four (4)
CUBIC INCH DISPLACEMENT	134
BORE X STROKE	3.43" x 3.64
RPM	1,800
DIMENSIONS	L 43.25" x W 21" x H 26"
WEIGHT	775 lbs Shipping Wt. 957 Lbs
NEWAGE / STANFORD	BCI 184 E 60 Hertz
OUTPUT VOLTS	120 / 240, Single Phase
OUTPUT AMPS	175 / 87.5
OUTPUT WATTS	21,000
EXHAUST DIAM.	2.0" Flange Female NPT
FUEL LINE	5/16
FUEL RETURN	3/16

STANDARD FEATURES

- 12 Volt Electric Starter
- 12 Volt Battery Charging Alternator
- Automatic Engine Shutdown for Low Oil Pressure & High Coolant Temp
- Fuel Filter
- Fuel Transfer Pump
- Air Silencer Intake-Cleaner
- Heavy Duty Steel Frame
- Single Bearing Generator
- Brushless Excitor
- Start / Stop / Preheat
- Hourmeter

Florida
2880 Hammondville Road
Pompano Beach, Florida 33069
Phone: (954) 979-5899
Fax: (954) 979-4349

Connecticut
900 Industrial Park Road. Suite #10
Deep River, Connecticut 06417
Phone: (860) 526-9773
Fax: (860) 526-2090