

ESS-11.0 KW

EMERGENCY STATIONARY STANDBY

MODEL	EPA CERTIFIED	ESS-11.0 KW
ENGINE	KUBOTA	D1305-E4BG
CYLINDERS		THREE (3)
H.P. @ 1800 RPM		17.6
CUBIC INCH		76.95
BORE & STROKE		3.07 x 3.46
ASPIRATION		NATURAL
COOLING SYSTEM		RADIATOR COOLED
EXHAUST	2.0"	MUFFLER / RESIDENTIAL
SPECIFICATIONS		L 37.0 x W 20.0 x H 29.0
WEIGHT		600LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		91.6/45.8
OUTPUT WATTS		11,000

STANDARD FEATURE

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL FRAME
SINGLE BEARING GENERATOR
DONALDSON AIR INTAKE SILENCER / FILTER
BRUSHLESS EXCITOR
START/STOP/PREHEAT/HOURMETER
RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONTROLLER	AC-DC-DIGITAL-AUTOSTART MODULE
THREE PHASE ELECTRICAL END	
CIRCUIT BREAKER	
BATTERY, RACK, & CABLES	(mounted on machine)
2 AMP BATTERY CHARGER	(mounted on machine)
FUEL MOUNTED BASE TANK	60 GALLON & 100 GALLON
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED	SINGLE WALL
ELECTRIC FUEL PUMP	