

ESS-15.0 KW

EMERGENCY STATIONARY STANDBY

MODEL		ESS-15.0 KW
ENGINE	KUBOTA	D1703-ME4BG
CYLINDER		THREE (3)
CUBIC INCH		100.5
BORE & STROKE		3.43 x 3.64
H.P. @ 1800 RPM		24.3 H.P.
ASPIRATION		NATURAL
COOLING SYSTEM		RADIATOR COOLED
EXHAUST	2.0"	MUFFLER (shipped loose)
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 44.0 x W 25.0 x H 34.0
WEIGHT		750 LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		125 / 62.50
OUTPUT WATTS		15,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / FILTER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START / STOP / PREHEAT / HOURMETER (mounted on machine)
RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONTROLLER AC-DC-DIGITAL-AUTOSTART MODULE
THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
BATTERY, RACK, & CABLES (mounted on machine)
2 AMP BATTERY CHARGER (mounted on machine)
FUEL MOUNTED BASE TANK 60 GALLON & 100 GALLON SINGLE WALL
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED
ELECTRIC FUEL PUMP