

ESS-30.0 KW

EMERGENCY STATIONARY STANDBY

MODEL	EPA CERTIFIED	ESS-30.0 KW
ENGINE	KUBOTA	V3300-E3BG
CYLINDERS		FOUR (4)
H.P. @ 1800 RPM		45.1
CUBIC INCH		202.48
BORE & STROKE		3.86 x 4.33
ASPIRATION		NATURAL
COOLING SYSTEM		RADIATOR COOLED
EXHAUST	2'5"	MUFFLER / RESIDENTIAL
SPECIFICATIONS		L 60.0 x W 30.0 x H 40.0
WEIGHT		1225LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		250 / 125
OUTPUT WATTS		30,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START/STOP / PREHEAT / HOURMETER
RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONTROLLER **AC-DC-DIGITAL-AUTOSTART MODULE**
THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
BATTERY, RACK, & CABLES **(mounted on machine)**
2 AMP BATTERY CHARGER **(mounted on machine)**
FUEL MOUNTED BASE TANK **200 GALLON** **SINGLE WALL**
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED
ELECTRIC FUEL PUMP