

ESS-50.0 KW

EMERGENCY STATIONARY STANDBY

MODEL		ESS-50.0 KW
ENGINE	KUBOTA	V3800DI-T-E3BG
CYLINDER		FOUR (4)
CUBIC INCH		230
BORE & STROKE		3.94 x 4.72
H.P. @ 1800 RPM		70.8
ASPIRATION		TURBO CHARGED
COOLING SYSTEM		RADIATOR COOLED
EXHAUST	2.0"	MUFFLER (shipped loosed)
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 68.0 x W 36.0 x H 40.0
WEIGHT		1,445
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		208 V / Three Phase
OUTPUT AMPS		138.95
OUTPUT WATTS		50,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / FILTER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
START / STOP / PREHEAT / HOURMETER (mounted on machine)
RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONTROLLER AC-DC-DIGITAL-AUTOSTART MODULE
SINGLE PHASE ELECTRICAL END
CIRCUIT BREAKER
BATTERY, RACK, & CABLES (mounted on machine)
2 AMP BATTERY CHARGER (mounted on machine)
FUEL MOUNTED BASE TANK 200 GALLON SINGLE WALL
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED
ELECTRIC FUEL PUMP