## **ESS-60.0 KW**

## **EMERGENCY STATIONARY STANDBY**

MODEL ESS-60.0 KW

ENGINE JOHN DEERE 4045TF280
CYLINDER FOUR (4)

CUBIC INCH 275

BORE & STROKE 4.19 x 5.00 H.P. @ 1800 RPM 90.0 H.P.

ASPIRATION TURBO CHARGE

COOLING SYSTEM RADIATOR COOLED

EXHAUST 3.5" MUFFLER (shipped loose)

FUEL INLET 3/8"
FUEL RETURN 1/4"

**DIMENSIONS** L 68.0 x W 36.0 x H 48.0

WEIGHT 2200 LBS

MODELSTAMFORD/NEWAGEOUTPUT VOLTS208 V / THREE PHASE

OUTPUT AMPS 167.0
OUTPUT WATTS 60,000

## **STANDARD FEATURES**

12 VOLT DC START / CHARGING

AUTOMATIC ENGINE SHUTDWON FOR LOW OIL & HIGH COOLANT TEMPERATURE

**FUEL FILTER** 

**FUEL TRANSFER PUMP** 

AIR INTAKE SILENCER / FILTER

FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

BRUSHLESS EXCITOR
RESIDENTIAL MUFFLER

## **OPTIONAL EQUIPMENT**

CONTROLS INC. CONTROLLER AC-DC-ELECTRONIC-AUTOSTART MODULE

SINGLE PHASE ELECTRICAL END

CIRCUIT BREAKER
BATTERY CHARGER

BATTERY, RACK, & CABLES (mounted on machine)
FUEL MOUNTED BASE TANK 200/300/500 GALLON

POWDER COATED ALUMINUM ENCLOSURE