

JD4-65.0 KW

KEEL COOLED / WET MANIFOLD

MODEL	MARINE CERTIFIED	JD4-65.0 KW
ENGINE	JOHN DEERE	4045TFM85
CYLINDERS		FOUR (4)
CUBIC INCH		275
BORE & STROKE		4.17 x 5.00
H.P. @ 1800 RPM		99.0 H.P.
ASPIRATION		TURBOCHARGE
COOLING SYSTEM		KEEL COOLED / WET MANIFOLD
EXHAUST	3.0"	DRY EXHAUST FLANGE
FUEL INLET		3/8"
FUEL RETURN		1/4"
DIMENSIONS		L56.0 x W 32.0 x H 46.0
WEIGHT		2,375 LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		208 / THREE PHASE
OUTPUT AMPS		180.7
OUTOUT WATTS		65,000

STANDARD FEATURES

12 VOLT START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / CLEANER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITER

OPTIONAL EQUIPMENT

24 VOLT DC START / CHARGING
CONTROLS INC. CONTROLLER **ELECTRONIC AC-DC-DIGITAL READOUT**
CIRCUIT BREAKER MOUNTED
REMOTE START/STOP PANEL