

JD4-99.0 KW

KEEL COOLED / WET MANIFOLD

MODEL	MARINE CERTIFIED	JD4-99.0 KW
ENGINE	JOHN DEERE	4045AFM85
CYLINDERS		FOUR (4)
CUBIC INCH		273
BORE & STROKE		4.21 x 5.00
H.P. @ 1800 RPM		148 H.P.
ASPIRATION		TURBO CHARGE & AFTERCOOLED
COOLING SYSTEM		KEEL COOLED / WET
EXHAUST	3.0"	DRY EXHAUST FLANGE
FUEL INLET		3/8"
FUEL RETURN		1/4"
DIMENSIONS		L 68.0 x W 36.0 x H 38.5
WEIGHT		2,450 LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		208 / THREE PHASE
OUTPUT AMPS		274
OUTPUT WATTS		99,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER FUEL TRANSFER PUMP
AIR INTAKE SILENCER / CLEANER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITER

OPTIONAL EQUIPMENT

24 VOLT DC START / CHARGING
CONTROLS INC. CONTROLLER **ELECTRONIC AC-DC-DIGITAL READOUT**
CIRCUIT BREAKER
REMOTE START/STOP PANEL