KK3-9.5 KW

KEEL COOLED / DRY EXHAUST

MODEL KK3-9.5 KW

ENGINE KUBOTA D1105-E4BG

CYLINDERS THREE (3)
CUBIC INCH 68.53

BORE & STROKE 3.07 x 3.09

H.P. @ 1800 RPM 15.4

ASPIRATION NATURAL

COOLING PACKAGE KEEL COOLED / HOT MANIFOLD

EXHAUST 2.0" DRY EXHAUST FLANGE

FUEL INLET 5/16
FUEL RETURN 3/16

DIMENSIONS L 35.0 x W 24.0 X H 29.0

WEIGHT 550 LBS

MODELSTAMFORD/NEWAGEOUTPUT VOLTS120 / 240 / SINGLE PHASE

OUTPUT AMPS 79.17 / 39.58

OUTPUT WATTS 9,500

STANDARD FEATURES

12 VOLT DC START / CHARGING

AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE

FUEL FILTER

FUEL TRANSFER PUMP

AIR INTAKE SILENCER / CLEANER

FOUR POINT ISOLATION MOTOR MOUNTS

HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

BRUSHLESS EXCITOR

START / STOP / PREHEAT / HOURMETER (mounted on machine)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS

DC GAUGE PANEL W / START / STOP / 20FT EXTENSION HARNESS

THREE PHASE ELECTRICAL END

CIRCUIT BREAKER
ELECTRIC FUEL PUMP

WET EXHAUST MANIFOLD (mounted on engine)