KK4-21.0 KW

KEEL COOLED / DRY EXHAUST

MODEL MARINE CERTIFIED KK4-21.0 KW

ENGINE KUBOTA V2403-M-E3BG

 CYLINDERS
 FOUR (4)

 CUBIC INCH
 148.5

 BORE & STROKE
 3.43 x 4.03

 H.P. @ 1800 RPM
 35.5 H.P.

 ASPIRATION
 NATURAL

COOLING SYSTEM KEEL COOLED

EXHAUST 2.0" DRY EXHAUST FLANGE

FUEL INLET 5/16
FUEL RETURN 3/16

DIMENSIONS L 45.0 x 24.0 x H 30.0

WEIGHT 900 LBS

MODELSTAMFORD/NEWAGEOUTPUT VOLTS120 / 240 / SINGLE PHASE

 OUTPUT AMPS
 175 / 87.50

 OUTPUT WATTS
 21,000

STANDARD FEATURES

12 VOLT DC START / CHARGING

AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE

FUEL FILTER

FUEL TRANSFER PUMP

AIR INTAKE SILENCER / CLEANER

FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

BRUSHLESS EXCITOR

START / STOP / PREHEAT / HOURMETER (mounted on machine)

OPTIONAL EQUIPMENT

REMOTE START / STOP PANEL W / 20FT EXTENSION HARNESS
DC GAUGE PANEL WITH START / STOP / 20FT EXTENSION HARNESS

THREE PHASE ELECTRICAL END

CIRCUIT BREAKER
ELECTRIC FUEL PUMP

WET EXHAUST MANIFOLD (mounted on engine)