SEP-12.5 KW INDUSTRIAL GENERATOR

INDUSTRIAL / STANDBY

MODEL	EPA CERTIFIED	SEP4-12.5	
ENGINE	KUBOTA	V1505-E3BG	
CYLINDERS		FOUR (4)	
H.P. @ 1800 RPM		20.2	
CUBIC INCH		91.41	
BORE & STROKE		3.07 x 3.09	
ASPIRATION		NATURAL	
COOLING SYSTEM		RADIATOR COOLED	
EXHAUST	2.0"	MUFFLER / RESIDENTIAL	
SPECIFICATIONS		L 43.0 x W 20.0 x H 29.0	
WEIGHT		630LBS	
MODEL		STAMFORD/NEWAGE	
OUTPUT VOLTS		120 / 240 / SINGLE PHASE	
OUTPUT AMPS		104 / 52	
OUTPUT WATTS		12,500	
	STANDARD FEATURE		
12 VOLT DC START / CHARGING			
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE			
FUEL FILTER			
FUEL TRANSFER PUMP			
FOUR POINT ISOLATION MOTOR MOUNTS			
HEAVY DUTY STEEL FRAME			
SINGLE BEARING GENERATOR			
DONALDSON AIR INTAKE SILENCER / FILTER			
BRUSHLESS EXCITOR			
START/STOP/PREHEAT/HOURMETER			
RESIDENTIAL MUFFLER			
OPTIONAL EQUIPMENT			
CONTROLS INC. ELECT	RONIC CONTROLLER	AC-DC-DIGITAL-AUTOSTART I	MODULE
THREE PHASE ELECTRICAL END			
CIRCUIT BREAKER			
BATTERY, RACK, & CA		(mounted on machine)	
2 AMP BATTERY CHAP		(mounted on machine)	
FUEL MOUNTED BASE TANK 60 GALLON & 100 GALLON SINGLE WALL ENCLOSURE DOWNER COATED ALLIANUMA COUND ATTENUATED			
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED			
ELECTRIC FUEL PUMP			