

SEP3-20.0 KWCR

INDUSTRIAL / COMMERCIAL

MODEL			SEP-20.0 KWCR
ENGINE	KUBOTA	TIER IV	D1803-E4BG-CR
CYLINDER			THREE(3)
CUBIC INCH			111.4
BORE & STROKE			3.43 x 4.03
H.P. @ 1800 RPM			36.2
ASPIRATION			TURBO/CHARGE AIR COOLED
COOLING SYSTEM			RADIATOR COOLED
EXHAUST			DOC/MUFFLER
DIMENSIONS			L 58.0 x W 32.0 x H 43.0
WEIGHT			1291LBS
MODEL			PI144G/60 HERTZ
OUTPUT VOLTS			120 / 240 / SINGLE PHASE
OUTPUT AMPS			167 / 83.50
OUTPUT WATTS			20,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
AIR INTAKE SILENCER / FILTER
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
CONTROLS INC. CONTROL PANEL (mounted on machine)

OPTIONAL EQUIPMENT

THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
BATTERY, RACK, & CABLES
2 AMP BATTERY CHARGER
FUEL MOUNTED BASE TANK 100 GALLON SINGLE WALL
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED
ELECTRIC FUEL PUMP