

SEP4-30.0 KWCR

INDUSTRIAL / COMMERCIAL

MODEL	EPA CERTIFIED	TIERIV	SEP4-30.0 KWCR
ENGINE	KUBOTA		V2403-E4BG-CR
CYLINDERS			FOUR (4)
H.P. @ 1800 RPM			48.9
CUBIC INCH			148.90
BORE & STROKE			3.43x4.03
ASPIRATION			TURBOCHARGED/CHARGE AIR COOLED
COOLING SYSTEM			RADIATOR COOLED
EXHAUST			DOC/MUFFLER
SPECIFICATIONS			L 63.0 x W 32.0 x H 43.0
WEIGHT			1225LBS
MODEL			STAMFORD/NEWAGE
OUTPUT VOLTS			120 / 240 / SINGLE PHASE
OUTPUT AMPS			250 / 125
OUTPUT WATTS			30,000

STANDARD FEATURES

12 VOLT DC START / CHARGING
AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE
FUEL FILTER
FUEL TRANSFER PUMP
FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL FRAME
SINGLE BEARING GENERATOR
BRUSHLESS EXCITOR
CONTROLS INC. CONTROLLER
RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

THREE PHASE ELECTRICAL END
CIRCUIT BREAKER
BATTERY, RACK, & CABLES (mounted on machine)
2 AMP BATTERY CHARGER (mounted on machine)
FUEL MOUNTED BASE TANK 200 GALLON SINGLE WALL
ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED
ELECTRIC FUEL PUMP