SEP-7.0 KW

INDUSTRIAL / STANDBY

MODEL SEP3-7.0 KW

ENGINE KUBOTA D1005-E3BG

CYLINDER THREE (3)
CUBIC INCH 61.08

BORE & STROKE 2.99 x 2.90

H.P. @ 1800 RPM 13.1
ASPIRATION NATURAL

COOLING SYSTEM RADIATOR COOLED

EXHAUST 2.0" MUFFLER (shipped loose)

FUEL INLET 5/16
FUEL RETURN 3/16

DIMENSIONS L 40.0 x W 20.0 x H 29.0

WEIGHT 550LBS

MODELSTAMFORD/NEWAGEOUTPUT VOLTS120 / 240 / SINGLE PHASE

OUTPUT AMPS 58 / 29
OUTPUT WATTS 7,000

STANDARD FEATURES

12 DC START / CHARGING

AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE

FUEL FILTER

FUEL TRANSFER PUMP

AIR INTAKE SILENCER / FILTER

FOUR POINT ISOLATION MOTOR MOUNTS
HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

BRUSHLESS EXCITOR

START / STOP / PREHEAT / HOURMETER (mounted on machine)

RESIDENTIAL MUFFLER

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONTROLLER AC-DC-DIGITAL-AUTOSTART MODULE

THREE PHASE ELECTRICAL END

CIRCUIT BREAKER

BATTERY, RACK, & CABLES (mounted on machine)
2 AMP BATTERY CHARGER (mounted on machine)

FUEL MOUNTED BASE TANK 60 GALLON & 100 GALLON SINGLE WALL

ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED

ELECTRIC FUEL PUMP