## **SEP-8.5 KW**

## INDUSTRIAL / STANDBY

MODEL SEP3-8.5 KW

ENGINE KUBOTA D1105-E4BG

CYLINDER FOUR (4)
CUBIC INCH 68.53
BORE & STROKE 3.07 x 3.09

H.P. @ 1800 RPM 15.4

**ASPIRATION NATURAL** 

COOLING SYSTEM RADIATOR COOLED

EXHAUST 2.0" MUFFLER ( shipped loose )

FUEL INLET 5/16
FUEL RETURN 3/16

DIMENSIONS L 40.0 x W 20.0 x H 29.0

WEIGHT 550LBS

MODEL STAMFORD/NEWAGE
OUTPUT VOLTS 120 / 240 / SINGLE PHASE

OUTPUT AMPS 70 / 35
OUTPUT WATTS 8,500

## STANDARD FEATURES

12 VOLT DC START / CHARGING

AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE

**FUEL FILTER** 

**FUEL TRANSFER PUMP** 

AIR INTAKE SILENCER / FILTER

FOUR POINT ISOLATION MOTOR MOUNTS HEAVY DUTY STEEL MOUNTING FRAME

SINGLE BEARING GENERATOR

**BRUSHLESS EXCITOR** 

START / STOP / PREHEAT / HOURMETER (mounted on machine)

**RESIDENTIAL MUFFLER** 

**OPTIONAL EQUIPMENT** 

CONTROLS INC. ELECTRONIC CONTROLLER AC-DC-DIGITAL-AUTOSTART MODULE

THREE PHASE ELECTRICAL END

**CIRCUIT BREAKER** 

BATTERY, RACK, & CABLES (mounted on machine)
2 AMP BATTERY CHARGER (mounted on machine)

FUEL MOUNTED BASE TANK 60 GALLON & 100 GALLON SINGLE WALL

ENCLOSURE, POWDER COATED ALUMINUM, SOUND ATTENUATED

**ELECTRIC FUEL PUMP**