SEP-9.5 KW

INDUSTRIAL / STANDBY

MODEL		SEP3-9.5 KW
ENGINE	КИВОТА	D1105-E4BG
CYLINDER		THREE (3)
CUBIC INCH		68.53
BORE & STROKE		3.07 x 3.09
H.P. @ 1800 RPM		15.4
ASPIRATION		NATURAL
COOLING SYSTEM		RADIATOR COOLED
EXHAUST	2.0"	MUFFLER (shipped loose)
FUEL INLET		5/16
FUEL RETURN		3/16
DIMENSIONS		L 37.0 x W 20.0 x H 29.0
WEIGHT		550LBS
MODEL		STAMFORD/NEWAGE
OUTPUT VOLTS		120 / 240 / SINGLE PHASE
OUTPUT AMPS		80 / 40
OUTPUT WATTS		9,500
	STANDARD FEATURES	

12 VOLT DC START / CHARGING AUTOMATIC ENGINE SHUTDOWN FOR LOW OIL & HIGH COOLANT TEMPERATURE FUEL FILTER FUEL TRANSFER PUMP AIR INTAKE SILENCER / FILTER FOUR POINT ISOLATION MOTOR MOUNTS HEAVY DUTY STEEL MOUNTING FRAME SINGLE BEARING GENERATOR **BRUSHLESS EXCITOR** START / STOP / PREHEAT / HOURMETER (mounted on machine) **RESIDENTIAL MUFFLER**

OPTIONAL EQUIPMENT

CONTROLS INC. ELECTRONIC CONT	TROLLER AC-DC-DIGITAL-AUTOST	ART MODULE	
THREE PHASE ELECTRICAL END			
CIRCUIT BREAKER			
BATTERY, RACK, & CABLES	(mounted on machine)	(mounted on machine)	
2 AMP BATTERY CHARGER	(mounted on machine)		
FUEL MOUNTED BASE TANK	60 GALLON & 100 GALLON	SINGLE WALL	
ENCLOSURE, POWDER COATED AL	UMINUM, SOUND ATTENUATED		
ELECTRIC FUEL PUMP			